



Position	Qty.	Description
----------	------	-------------

1

SP 30-6



Note! Product picture may differ from actual product

Product No.: [13A01906](#)

Submersible borehole pump, suitable for pumping clean water. Can be installed vertically or horizontally. All steel components are made in stainless steel, EN 1.4301 (AISI 304), that ensures high corrosive resistance. This pump carries drinking water approval.

The pump is fitted with a 5.5 kW MS4000 motor with sand shield, mechanical shaft seal, water-lubricated journal bearings and a volume compensating diaphragm. The motor is a canned type submersible motor offering good mechanical stability and high efficiency. Suitable for temperatures up to 40 °C.

The motor is fitted with the Grundfos Tempcon sensor that, by use of powerline communication together with a MP204 control panel, enables temperature monitoring.

The motor is for direct-on-line starting (DOL).

Further product details

The pump is suitable for applications similar to the following:


- raw-water supply
- irrigation
- groundwater lowering
- pressure boosting
- fountain applications.

The Grundfos SP pump is renowned for its high efficiency and already complies with the requirements of the Minimum Efficiency Index, and therefore Grundfos is amongst the best in class within submersible pumps.



Pump

All pump surfaces that are in contact with pumped liquids are made in stainless steel which makes them corrosion- and wear-resistant. The corrosion diagram below shows the capabilities of the pump and motor in relation to the temperature in Celsius (y-axis) and the concentration of chloride in ppm (x-axis).



The elastomer parts in the pump are made of NBR (Nitrile-Butadiene Rubber) which ensures good wear resistance and long service intervals.

In case the pump is used for pumping water with high content of hydrocarbons or solvents, Grundfos offers FKM rubber parts (Fluorocarbon) which are oil and temperature-resistant up to 90 °C.

The pump is built with octagonal bearings with sand flush channels that minimise wear. As wear of the pump is inevitable, the pump design allows for easy replacement of all internal wear parts (bearings, impeller, wear rings and seal rings) to maintain high performance and a long lifetime.

The suction interconnector is fitted with a strainer to prevent large particles from entering the pump. The suction interconnector is designed to comply with NEMA standards for motor mounting/dimensions.

Motor

The stator is hermetically encapsulated in stainless steel and the windings are embedded in polymer compound. This results in high mechanical stability, optimum cooling and reduces the risk of short circuits in the windings.

The shaft seal is a tungsten carbide/ceramic replaceable mechanical shaft seal. The material combination provides optimum sealing, resistance and long life. Together with the shaft seal housing, the sand shield forms a labyrinth seal, which during normal operating conditions prevents penetration of sand particles into the shaft seal.

The motor is fitted with the Grundfos Tempcon temperature sensor device that includes a NTC-resistor which senses the temperature. The resistor is built-in close to the winding. The temperature is converted into a high-frequency signal which is sent via the submersible drop cable and which can be converted into a temperature reading by means of Grundfos MP204.

The MP204 is an electronic motor protection device that also monitors the supply network quality to protect the submersible motor against supply network disturbances.



Liquid:

Maximum liquid temperature: 40 °C

Max liquid t at 0.15 m/sec: 40 °C

Technical:

Speed for pump data: 2900 rpm

Rated flow: 30 m³/h

Rated head: 46 m



Shaft seal for motor: HM/CER



Position	Qty.	Description
		Curve tolerance: ISO9906:2012 3B Materials: Pump: Stainless steel EN 1.4301 Pump housing: ASTM 304 Impeller: Stainless steel EN 1.4301 ASTM 304 Motor: Stainless steel DIN W.-Nr. 1.4301 AISI 304 Installation: Pump outlet: RP3 Motor diameter: 4 inch Electrical data: Motor type: MS4000 Rated power - P2: 5.5 kW 5.5 kW Mains frequency: 50 Hz Rated voltage: 3 x 380-400-415 V Start. method: direct-on-line Rated current: 13,0-13,0-13,4 A Starting current: 480-530-550 % Cos phi - power factor: 0,85-0,81-0,76 Rated speed: 2850-2860-2870 rpm Enclosure class (IEC 34-5):: IP68 Insulation class (IEC 85): F Built-in temp. transmitter: yes Others: Minimum efficiency index, MEI : 0.50 ErP status: EuP Standalone/Prod. Net weight: 42.8 kg Gross weight: 68 kg Shipping volume: 0.204 m ³



13A01906 SP 30-6 50 Hz








Company name:

Created by:

Phone:


Date:

Description	Value
General information:	
Product name:	SP 30-6
Position:	
Product No:	13A01906
EAN number:	5700390381103
Price:	On request
Technical:	
Speed for pump data:	2900 rpm
Rated flow:	30 m³/h
Rated head:	46 m
Impeller reduc.:	NONE
Shaft seal for motor:	HM/CER
Curve tolerance:	ISO9906:2012 3B
Stages:	6
Model:	B
Valve:	YES
Materials:	
Pump:	Stainless steel EN 1.4301
Pump housing:	ASTM 304
Impeller:	Stainless steel EN 1.4301 ASTM 304
Motor:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Installation:	
Pump outlet:	RP3
Motor diameter:	4 inch
Liquid:	
Maximum liquid temperature:	40 °C
Max liquid t at 0.15 m/sec:	40 °C
Electrical data:	
Motor type:	MS4000
Applic. motor:	GRUNDFOS
Rated power - P2:	5.5 kW 5.5 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-400-415 V
Start. method:	direct-on-line
Rated current:	13,0-13,0-13,4 A
Starting current:	480-530-550 %
Cos phi - power factor:	0,85-0,81-0,76
Rated speed:	2850-2860-2870 rpm
Enclosure class (IEC 34-5):::	IP68
Insulation class (IEC 85):	F
Motor protec:	NONE
Thermal protec:	external
Built-in temp. transmitter:	yes
Motor No:	79195511
Others:	
Minimum efficiency index, MEI :	0.50
ErP status:	EuP Standalone/Prod.
Net weight:	42.8 kg
Gross weight:	68 kg
Shipping volume:	0.204 m³






13A01906 SP 30-6 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.



13A01906 SP 30-6 50 Hz



Note! All units are in [mm] unless others are stated.

GRUNDFOS®



Company name:

Created by:

Phone:

Date:

Order Data:

Product name: SP 30-6

Amount: 1

Product No: 13A01906

Price: On request

Total: Price on request
